

Boiswood
GAS AND LIQUID CONTROL TECHNOLOGIES

Pressure & Vacuum
Flow
Level & Temperature
Tube & Fittings
HVACR
Custom Services




Type 100/200



MATERIAL	ND	PN	Set Pressure	CLASS	Set Pressure
CAST IRON	ND20 to ND80	PN16	0,25 to 16 bar		
	ND100	PN16	0,25 to 15 bar		
	ND125	PN16	0,25 to 9 bar		
	ND150	PN16	0,25 to 8 bar		
CARBON STEEL	ND20 à ND50	PN40	0,25 to 40 bar	150 300	0,25 to 20 bar 0,25 to 50 bar
	ND65	PN16	0,25 to 16 bar		
	ND80 à ND100	PN40	0,25 to 40 bar	150	0,25 to 20 bar
		PN16	0,25 to 16 bar	300	0,25 to 25 bar
	ND125	PN40	0,25 to 25 bar		
		PN16	0,25 to 16 bar		
	ND150	PN40	0,25 to 16 bar	150	0,25 to 10 bar
		PN16	0,25 to 10 bar	300	0,25 to 10 bar
STAINLESS STEEL	ND20 à ND50	PN40	0,25 to 39 bar	150 300	0,25 to 18 bar 0,25 to 49 bar
	ND65	PN16	0,25 to 15 bar		
	ND80	PN40	0,25 to 39 bar	150	0,25 to 18 bar
		PN16	0,25 to 15 bar	300	0,25 to 40 bar
	ND100	PN40	0,25 to 39 bar	150	0,25 to 18 bar
		PN16	0,25 to 15 bar	300	0,25 to 25 bar
	ND125	PN40	0,25 to 25 bar		
		PN16	0,25 to 15 bar		


TYPE 110-130

TIGHT PLUG WITHOUT LEVER




TYPE 120-140

TIGHT PLUG WITH LEVER



TYPE 200

COUNTERWEIGHT



Connection






RAISED FACE CLASS 150/300
PN 16/40

MALE FEMALE FACING

TONGUE GROOVE FACING

MALE FEMALE FACING

TONGUE GROOVE FACING



Special design



**PTFE
INTERNAL
PARTS**



EDF NUCLEAR



**EPOXY
PAINTING**



**WITH
PROXIMITY
DETECTOR**

Order information

MODEL	PLUG	SEAT/NOZZLE	MATIERE	CONNECTION	OPTIONS	PN 16/40	DN CI 150/300
1	1 TIGHT WITHOUT LEVER	0 SEAT	A - STEEL	R - PN 40	DISC JEP : O'RING EPDM JT : O'RING - FPM ON MODELS AR-IR - EPDM ON MODEL FR JK : O'RING KALREZ® T : PTFE	DN 20	04 (3/4")
	2 TIGHT WITH LEVER					DN 25	10 (1")
	1 TIGHT WITHOUT LEVER		1 - CLASS 150	DN 32		11 (1.1/4")	
	2 TIGHT WITH LEVER			DN 40		13 (1.1/2")	
	1 TIGHT WITHOUT LEVER	2 - PN 16	DN 50	20 (2")			
	2 TIGHT WITH LEVER		DN 65	23 (2.1/2")			
	1 TIGHT WITHOUT LEVER	1 FULL NOZZLE	I- STAINLESS STEEL	TIGHTNESS [ST : STELLITED SEAT PHC : HASTELLOY C2000® SEAT	DN 80	30 (3")	
	2 TIGHT WITH LEVER				DN 100	40 (4")	
	1 TIGHT WITHOUT LEVER				3 - CLASS 300	DN 125	50 (5")
	2 TIGHT WITH LEVER					DN 150	60 (60")