

## Large Size – Engineered Plastics

### Select from these Engineered Plastics for Aggressive or Ultra-Pure Liquids

Each of these series offers unique features. Choose from this selection when all-plastic material is desirable and tank space is not restricted.

LS-30 Series–  
Polysulfone



For water-based liquids, with limited use in oils and chemicals. Cost is suited for high volume OEM use. Polysulfone material of construction complies with FDA food contact regulations.

LS-74780 –  
All CPVC



Particularly well suited for rough service. Ideal for use in chemical and plating applications.

LS-1900TFE




Resists build-up of foreign material or sticky media. Float travel remains uninhibited in viscous or corrosive liquids. SPDT switch.

LS-1700TFE



A medium-size solution for ultra-pure liquid level sensing. Made of corrosion resistant PTFE for low particle generation.

### Dimensions



†L<sub>1</sub> = Switch actuation level, nominal (based on a liquid specific gravity of 1.0 and N.O. dry circuit—dimension will vary for N.C. circuit).

### Common Specifications

**Electrical Termination:** No. 18 AWG, 24" L., Lead Wires (Jacket material is indicated on dimensional drawings, above).

**Approvals:** LS-30 Series switches are U.L. Recognized – File No. E45168.

### How To Order – Select Part Number based on specifications required.

Series Number	Materials		Min. Liquid Sp. Gr.	Operating Temperature	Pressure, PSI, Max.	Switch*	Part Number	
	Stem, Mounting and Other Wetted	Float					Mounting Size	
							1/4" NPT	1/8" NPT
LS-30	Polysulfone with 316 S.S. Retaining Clip		.55	-40°F to +225°F (-40°C to +107.2°C)	50	SPST, 20 VA	<b>46201**</b>	—
						SPST, 100 VA	<b>46202**</b> ⚡	—
						SPDT, 20 VA	<b>46203</b>	—
LS-74780	CPVC		.85	-40°F to +180°F (-40°C to +82.2°C)	15	SPST, 20 VA	<b>74780**</b> ⚡	—
LS-1900TFE	Teflon®		.80	-40°F to +300°F (-40°C to +148.9°C)	30	SPDT, 20 VA	<b>133299</b> ⚡	—
LS-1700TFE	PTFE		.86	+32°F to +212°F (0°C to +100°C)	25	SPST, 20 VA, N.O.	—	<b>174100</b>
						SPST, 20 VA, N.C.	—	<b>174200</b>

\* See "Electrical Data" on Page X-5 for more information.

\*\* Switch operation is selectable, N.O. or N.C., by inverting the float on the unit stem. Units are shipped N.O. unless otherwise specified.

†† 100 VA switches are not U.L. Recognized.

⚡ – Stock Items.