

# BOISWOOD

## GAS AND LIQUID CONTROL TECHNOLOGIES

Pressure & Vacuum

Flow

Level & Temperature

Tube & Fittings

HVAC

Custom Services



## Level & Temperature Products Catalogue

At Boiswood we are trusted suppliers of products from world-leading manufacturers, always striving to deliver excellence across everything we do to ensure you look no further for your immediate and future requirements.

Whatever market you're in, we have unbeatable experience across a wide range of industries, backed by a team of professionals who are technically trained to offer you the best solutions for your specific applications.

Boiswood products are used by many of the UK's leading companies, across a range of applications and industries which include:

- **Gas Turbines**
- **Water Ballast Systems**
- **Food & Beverage**

Our products are also supported by a wide range of custom services which include product installation and selection training, component sub-assembly and fabrication, site leakage surveys and anthropology days – all designed to help you to reduce your overall costs.

**Whatever your needs, contact us for a quote today.**

LEVEL & TEMPERATURE



**In this section you will find details on the following products:**

- Bleeding and Venting Valves ..... 69
- Electro Optic Level Sensors and Switches ..... 70
- Float Valves ..... 71
- Level Indicators ..... 73
- Level Meters and Transmitters ..... 73
- Multiple Point Level Sensors and Switches ..... 74
- Single Point Level Sensors and Switches ..... 74
- Steam Traps ..... 77
- Submersible Transducers ..... 78
- Tank Bottom Valves ..... 79
- Thermometers ..... 79
- Wires and Seals ..... 80



## Bleeding and Venting Valves



Connections	Nominal Pressure	Operating Pressures	Max KVS Values	Max Working Temperature
<b>EB1.10 &amp; 1.11 CONTINUOUS BLEEDING AND VENTING VALVE</b>				
DN 32/15 DN 100/50	PN40	0 - 40 BAR	2440 Nm <sup>3</sup> /h	200°C



<b>EB1.12 CONTINUOUS BLEEDING AND VENTING VALVE</b>				
DN 25 - 100 G 1/2" - 2"	PN16	0 - 16 BAR	248 Nm <sup>3</sup> /h	130°C



<b>EB1.20 CONTINUOUS BLEEDING AND VENTING VALVE</b>				
DN 80/65 DN 200/150	PN16 - 40	0 - 40 BAR	77770 Nm <sup>3</sup> /h	200°C



<b>EB1.32 CONTINUOUS BLEEDING AND VENTING VALVE</b>				
G 3/4" x G 1/2"	PN16	0 - 16 BAR	5.9 m <sup>3</sup> /h	130°C



<b>EB1.48 CONTINUOUS BLEEDING AND VENTING VALVE</b>				
G 1/2"	PN16	0 - 16 BAR	28 Nm <sup>3</sup> /h	130°C



<b>EB1.57 CONTINUOUS BLEEDING AND VENTING VALVE</b>				
DN 100	PN10	0 - 10 BAR	190 Nm <sup>3</sup> /h	130°C



<b>EB1.59 COMBINED BLEEDING AND VENTING VALVE</b>				
DN 100	PN10	0 - 10 BAR	62 Nm <sup>3</sup> /h	60°C



<b>EB1.74 COMBINED BLEEDING AND VENTING VALVE</b>				
DN 50 - 150	PN16	0 - 8 BAR	1783 Nm <sup>3</sup> /h	130°C



<b>EB1.75 COMBINED BLEEDING AND VENTING VALVE</b>				
DN 50 - 200 G 1" - 2"	PN16 - 40	0.3 - 40 BAR	7600 Nm <sup>3</sup> /h (Venting) 6100 Nm <sup>3</sup> /h (Bleeding)	60°C



<b>EB1.84 COMBINED BLEEDING AND VENTING VALVE</b>				
DN 50 - 150	PN10 - 16	0 - 16 BAR	1100 Nm <sup>3</sup> /h	130°C



<b>EB1.85 COMBINED BLEEDING AND VENTING VALVE</b>				
DN 50 - 200 G 2"	PN10 - 16	0.3 - 16 BAR	4200 Nm <sup>3</sup> /h (Venting) 4100 Nm <sup>3</sup> /h (Bleeding)	70°C



## Bleeding and Venting Valves



Connections	Nominal Pressure	Operating Pressures	Max KVS Values	Max Working Temperature
<b>EB3.50 STARTUP BLEEDING AND VENTING VALVE</b>				
DN 100 - 300	PN40	0 - 40 BAR	10708 Nm <sup>3</sup> /h	130°C



<b>EB3.51 STARTUP BLEEDING AND VENTING VALVE</b>				
DN 25 - 100	PN16	0 - 16 BAR	1070 Nm <sup>3</sup> /h	80°C



<b>EB3.52 STARTUP BLEEDING AND VENTING VALVE</b>				
DN 25 - 100	PN16	0 - 13 BAR	1935 Nm <sup>3</sup> /h	130°C



<b>EB6.54 COMBINED BLEEDING AND VENTING VALVE</b>				
DN 25 - 300	PN6 - 40	0.3 - 40 BAR	18550 Nm <sup>3</sup> /h	130°C

## Electro Optic Level Sensors and Switches



Connections	Pressure Ranges	Output	Materials	Max Working Temperature
<b>ELS1100 GENERAL ELECTRO OPTIC LEVEL SWITCH</b>				
1/4" NPT 3/8" Conduit 1/2" Straight Thread	0 - 150 psi	Open Collector	Polysulfone Nylon	-17.8 to +80°C



<b>ELS1100FLG FLANGED ELECTRO OPTIC LEVEL SWITCH</b>				
1/4" or 6mm Flanged	0 - 150 psi	Open Collector	Polysulfone	-17.8 to +80°C



<b>ELS1100HT HIGH TEMPERATURE ELECTRO OPTIC LEVEL SWITCH</b>				
3/8" NPT	0 to 150 psi	Transistor with 10K Pull Up	Isoplast	-40 to +100°C



<b>ELS1100HTS HIGH TEMPERATURE ELECTRO OPTIC LEVEL SWITCH</b>				
3/8" NPT M16 x 2	0 to 150 psi	Transistor with 10K Pull Up	Isoplast	-40 to +100°C



<b>ELS1100TFE TEFLON ELECTRO OPTIC LEVEL SWITCH</b>				
1/4" NPT	0 - 150 psi	Open Collector	Teflon	-17.8 to +80°C



<b>ELS1150 COMPACT ELECTRO OPTIC LEVEL SWITCH</b>				
1/2" NPT 3/4"-16 Straight Thread	0 - 2500 psi	Open Collector	Stainless Steel Nickel-Plated Steel	-40 to +100°C



## Electro Optic Level Sensors and Switches



Connections	Pressure Ranges	Output	Materials	Max Working Temperature
-------------	-----------------	--------	-----------	-------------------------

### ELS1150XP EXPLOSION PROOF ELECTRO OPTIC LEVEL SWITCH

1/2" NPT	0 - 5000 psi	Open Collector	Stainless Steel Nickel Plated Steel	-40 to +125°C
----------	--------------	----------------	--	---------------



### ELS1200 SERIES HIGH PRESSURE ELECTRO OPTIC LEVEL SWITCH

1/2" NPT	0 - 2500 psi	Transistor with 10K Pull Up	Zinc Nickel Plated Steel	-40 to +100°C
----------	--------------	--------------------------------	--------------------------------	---------------



### ELS1200CR CORROSION RESISTANT ELECTRO OPTIC LEVEL SWITCH

1/2" NPT	0 - 2500 psi	Transistor with 10K Pull Up	Stainless Steel Hastelloy C	-40 to +100°C
----------	--------------	--------------------------------	--------------------------------	---------------



### ELS950 RUGGED ELECTRO OPTIC LEVEL SWITCH

1/4" MNPT 1/2"-20UNF-2B M12 x 1-8	0 - 250 psi	Sink 40 mA Max.	Polysulfone (Others on request)	-40 to +110°C
---	-------------	-----------------	---------------------------------------	---------------



### ELS950M RUGGED ELECTRO OPTIC LEVEL SWITCH

1/4" MNPT 1/2"-20UNF-2B M12 x 1-8	0 - 250 psi	Sink 40 mA Max.	Brass	-40 to +110°C
---	-------------	-----------------	-------	---------------

## Float Valves



Connections	Nominal Pressure	Operating Pressures	KVS Values	Max Working Temperature
-------------	------------------	---------------------	------------	-------------------------

### BV500 FLOAT TRAP

DN 15 - 50 G 1/2" - 2"	PN16	0 - 25 BAR	On Request	250°C
---------------------------	------	------------	------------	-------



### NV12 & 12P FLOAT VALVE

DN 20 - 150	PN16	0 - 8 BAR	2.8 - 195 m <sup>3</sup> /h	110°C
-------------	------	-----------	-----------------------------	-------



### NV15E FLOAT VALVE

DN 40 - 300	PN16	0 - 16 BAR	18 - 900 m <sup>3</sup> /h	70°C
-------------	------	------------	----------------------------	------



### NV16 FLOAT VALVE

DN 15 - 100	PN16 - 40	0 - 4 BAR	2.6 - 80 m <sup>3</sup> /h	130°C
-------------	-----------	-----------	----------------------------	-------

### NV16E FLOAT VALVE

DN 15 - 150	PN16 - 40	0 - 16 BAR	4 - 160 m <sup>3</sup> /h	130°C
-------------	-----------	------------	---------------------------	-------



### Float Valves



Connections	Nominal Pressure	Operating Pressures	KVS Values	Max Working Temperature
<b>NV26 FLOAT VALVE</b>				
DN 125 - 400	PN10 - 40	0 - 16 BAR	46 - 1800 m <sup>3</sup> /h	130°C

#### NV55 FLOAT VALVE

DN 15 - 100	PN16 - 40	0 - 4 BAR	2.6 - 80 m <sup>3</sup> /h	130°C
-------------	-----------	-----------	----------------------------	-------

#### NV55E FLOAT VALVE



DN 15 - 150	PN16 - 40	0 - 16 BAR	4 - 160 m <sup>3</sup> /h	130°C
-------------	-----------	------------	---------------------------	-------

#### NV56 FLOAT VALVE

DN 125 - 400	PN10 - 40	0 - 16 BAR	46 - 1800 m <sup>3</sup> /h	130°C
--------------	-----------	------------	-----------------------------	-------

#### NV66E FLOAT VALVE



DN 15 - 100	PN16	0 - 16 BAR	4 - 100 m <sup>3</sup> /h	130°C
-------------	------	------------	---------------------------	-------

#### NV67E FLOAT VALVE



DN 15 - 100	PN16	0 - 16 BAR	4 - 100 m <sup>3</sup> /h	130°C
-------------	------	------------	---------------------------	-------

#### NV71 FLOAT VALVE



DN 25 - 150	PN10	0 - 8 BAR	1.6 - 81 m <sup>3</sup> /h	300°C
-------------	------	-----------	----------------------------	-------

#### NV80 & 82 FLOAT VALVE



DN 15 - 200	PN16	0 - 8 BAR	1 - 115 m <sup>3</sup> /h	110°C
-------------	------	-----------	---------------------------	-------

#### NV93 FLOAT VALVE



DN 15 - 80	PN16	0 - 8 BAR	16 - 81 m <sup>3</sup> /h	300°C
------------	------	-----------	---------------------------	-------

#### NV94 FLOAT VALVE



G 3/8" - 1-1/2"	PN16	0 - 8 BAR	0.5 - 21 m <sup>3</sup> /h	300°C
-----------------	------	-----------	----------------------------	-------

#### NV95E FLOAT VALVE



G 1" - 1-1/4"	PN16	0 - 16 BAR	13 m <sup>3</sup> /h	70°C
---------------	------	------------	----------------------	------



## Float Valves

Connections	Nominal Pressure	Operating Pressures	KVS Values	Max Working Temperature
-------------	------------------	---------------------	------------	-------------------------

### NV98 FLOAT VALVE



DN 40 - 80 G 3/8" - 1-1/2"	PN16	0 - 8 BAR	0.5 - 82 m <sup>3</sup> /h	130°C
-------------------------------	------	-----------	----------------------------	-------

## Level Indicators

Connections	Operating Pressures	Materials	Accessories	Max Working Temperature
-------------	---------------------	-----------	-------------	-------------------------



### NMF MEMBRANE LEVEL MONITOR

M20 x 1.5	Up to 1 BAR (Overpressure)	NBR, Nitrile, FPM, Stainless Steel	N/A	Up to 200°C
-----------	-------------------------------	--	-----	-------------



### SURESITE HIGH PERFORMANCE LEVEL INDICATOR

MNPT Nipple FNPT Coupling ANSI Flange Weldneck/ Socketweld	Up to 4,200 PSI	316L Stainless Steel Titanium	Transmitters J-Box/Signal Conditioners Switch Modules	Up to 399°C
--	-----------------	-------------------------------------	--	-------------



### SURESITE MINIATURE LEVEL INDICATOR

MNPT Nipple FNPT Coupling ANSI Flange Sanitary Flange	Up to 400 PSI	316L Stainless Steel Aluminum	Transmitters Switch Modules Indicating Scales	Up to 204°C
--	---------------	-------------------------------------	---	-------------



### SURESITE STANDARD LEVEL INDICATOR

MNPT Nipple FNPT Coupling ANSI Flange	Up to 700 PSI	316L Stainless Steel Carpenter 20 Hastelloy C276	Transmitters J-Box/Signal Conditioners Switch Modules	Up to 399°C
---	---------------	---	--	-------------

## Level Meters and Transmitters

Connections	Operating Pressures	Materials	Measuring Length	Max Working Temperature
-------------	---------------------	-----------	------------------	-------------------------



### NGM RADAR LEVEL TRANSMITTER

NPT, BSPP or Flanged	-1 to +40 BAR	Stainless Steel	Up to 20m	-150 to +250°C
-------------------------	---------------	-----------------	-----------	----------------



### NGR GUIDED WAVE RADAR LEVEL TRANSMITTER

NPT or BSPP	-1 to +10 BAR	Stainless Steel	Up to 20m	-20 to +100°C
-------------	---------------	-----------------	-----------	---------------



### NIR ROTATING VANE LEVEL MONITOR

BSPP or Flanged	-0.5 to +0.5 BAR	Stainless Steel Aluminum	Up to 4m	-20 to +200°C
-----------------	------------------	-----------------------------	----------	---------------



## Level Meters and Transmitters



Connections	Operating Pressures	Materials	Measuring Length	Max Working Temperature
-------------	---------------------	-----------	------------------	-------------------------

### NRM NON CONTACT RADAR LEVEL TRANSMITTER

NPT, BSPP, Pipe Coupling, Tri-Clamp or Flanged	Up to 25 BAR	Polypropylene Aluminum Stainless Steel	Up to 23m	Up to 180°C
--	--------------	--	-----------	-------------



### NUS-4 ULTRASONIC LEVEL METER

NPT, BSPP or Flanged	Up to 3 BAR ABS	Polypropylene PVDF	Up to 25m (Liquids) Up to 10m (Solids)	Up to 90°C
----------------------	-----------------	-----------------------	---	------------



### NUS-7 ULTRASONIC LEVEL METER

NPT or BSPP	Up to 3 BAR ABS	Polypropylene PVDF	Up to 6m (Liquids)	Up to 80°C
-------------	-----------------	-----------------------	--------------------	------------

## Multiple Point Level Sensors and Switches



Connections	Operating Pressures	Materials	Measuring Length	Max Working Temperature
-------------	---------------------	-----------	------------------	-------------------------

### LS300A MULTIPLE POINT LEVEL SWITCH

NPT, BSPP or Flanged	Up to 300 psi	Polysulfone Noryl	Up to 50cm (1 to 4 Actuation Levels)	-40 to +121°C
----------------------	---------------	----------------------	--------------------------------------	---------------



### LS400E MULTIPLE POINT LEVEL SWITCH

BSPP, Flanges or Plug	Up to 20 BAR	Brass Stainless Steel	Up to 80cm (1 to 4 Actuation Levels)	-20 to +150°C
-----------------------	--------------	--------------------------	--------------------------------------	---------------



### LS800 MULTIPLE POINT LEVEL SWITCH

NPT or Flanged	Up to 750 psi	Brass Stainless Steel	Up to 3.4m (1 to 6 Actuation Levels)	-40 to +149°C
----------------	---------------	--------------------------	--------------------------------------	---------------



### LS800E MULTIPLE POINT LEVEL SWITCH

BSPP, Flanges or Plug	Up to 30 BAR	Brass Stainless Steel	Up to 3m (1 to 7 Actuation Levels)	-40 to +150°C
-----------------------	--------------	--------------------------	------------------------------------	---------------



### LS800PVC MULTIPLE POINT LEVEL SWITCH

NPT or Flanged	Up to 15 PSI	PVC	Up to 1.5m (1 to 7 Actuation Levels)	-17.8 to +51.7°C
----------------	--------------	-----	--------------------------------------	------------------

## Single Point Level Sensors and Switches



Connections	Operating Pressures	Materials	Output	Max Working Temperature
-------------	---------------------	-----------	--------	-------------------------









### CAP100 NON CONTACT CAPACITIVE LEVEL SENSOR

Non-Contact	On Request	Glass Filled Nylon	3 Wire PVC	-25 to +70°C
-------------	------------	--------------------	------------	--------------





## Single Point Level Sensors and Switches

Connections	Operating Pressures	Materials	Output	Max Working Temperature
<b>CAP150 CAPACITIVE LEVEL SENSOR</b>				
 M18 x 1	On Request	All-Valox Nickel Plated Brass	3 Wire PVC	-25 to +70°C
<b>CAP200 COMPACT CAPACITIVE LEVEL SENSOR</b>				
 1/2" NPT	Up to 150 psi	Delrin	3 Wire PVC	-25 to +70°C
<b>CAP300 CAPACITIVE LEVEL SENSOR</b>				
 NPT, SAE or Metric	Up to 100 psi	Brass 316L Stainless Steel	3-PIN Deutsch Flying Leads PVC Cable	-40 to +125°C
<b>EXOSENSE PIEZO RESONANT SENSOR</b>				
 Adhesive Cover	On Request	HPDE, LDPE, PP, PVC, ABS (Others on Request)	Mini USB	0 to +65°C
<b>LS1050E SINGLE POINT LEVEL SWITCH</b>				
 3/4" BSPP	Up to 16 BAR	Brass Stainless Steel	Cable	-40 to +100°C
<b>LS1700 SINGLE POINT LEVEL SWITCH</b>				
 1/8" NPT	Up to 1000 psi	Brass Stainless Steel	Lead Wires	-40 to +149°C
<b>LS1750 SINGLE POINT LEVEL SWITCH</b>				
 1/8" NPT	Up to 100 psi	Stainless Steel	Lead Wires	-40 to +204.4°C
<b>LS1755 SINGLE POINT LEVEL SWITCH</b>				
 1/8" NPT	Up to 275 psi	Stainless Steel	Lead Wires	-40 to +148.9°C
<b>LS1800 SINGLE POINT LEVEL SWITCH</b>				
 1/8" NPT or BSPP	Up to 10 BAR	Brass Stainless Steel	Cable Lead Wires	-40 to 110°C
<b>LS1900 SINGLE POINT LEVEL SWITCH</b>				
 1/4" NPT or BSPP	Up to 10 BAR	Brass Stainless Steel	Cable Lead Wires	-40 to 110°C
<b>LS1900T TEFLON SINGLE POINT LEVEL SWITCH</b>				
 1/4" BSPP	Up to 3 BAR	PTFE	Cable Lead Wires	-40 to 150°C



## Single Point Level Sensors and Switches

LEVEL & TEMPERATURE

Connections	Operating Pressures	Materials	Output	Max Working Temperature
-------------	---------------------	-----------	--------	-------------------------



### LS1950E ATEX SINGLE POINT LEVEL SWITCH

1/4" NPT or BSPP	Up to 30 BAR	Stainless Steel	Cable Lead Wires High Temp AWG	-40 to 200°C
------------------	--------------	-----------------	--------------------------------------	--------------



### LS2050E SIDE MOUNTED LEVEL SWITCH

1" BSPT	Up to 60 BAR	Stainless Steel	Cable Terminal Box	-40 to 150°C
---------	--------------	-----------------	-----------------------	--------------



### LS2403E BILGE WATER LEVEL SWITCH

Hex Nut	Up to 10 BAR	Stainless Steel	Cable	-40 to +80°C
---------	--------------	-----------------	-------	--------------



### LS270 SPECIALTY LEVEL SWITCH

Hex Nut	Up to 150 psi	Stainless Steel	Cable	-40 to +60°C
---------	---------------	-----------------	-------	--------------



### LS270E BILGE WATER LEVEL SWITCH

Hex Nut	Up to 10 BAR	Stainless Steel	Cable	-40 to +80°C
---------	--------------	-----------------	-------	--------------



### LS3 SINGLE POINT LEVEL SWITCH

NPT, BSPP or Metric	Up to 10 BAR	Polypropylene Nylon PVDF	Cable Lead Wires	-40 to +121°C
------------------------	--------------	--------------------------------	---------------------	---------------



### LS30 SINGLE POINT LEVEL SWITCH

1/4" NPT	Up to 50 psi	Polysulfone CPVC Teflon PTFE	Lead Wire	-40 to +148.9°C
----------	--------------	---------------------------------------	-----------	-----------------



### LS52100E SIDE MOUNTED LEVEL SWITCH

1" BSPT	Up to 35 BAR	Stainless Steel	Cable Terminal Box	-40 to +150°C
---------	--------------	-----------------	-----------------------	---------------



### LS6 SIDE MOUNTED LEVEL SWITCH

1/4" NPT	Up to 7 BAR	Polypropylene	Lead Wires	-40 to 107°C
----------	-------------	---------------	------------	--------------



### LS7 SIDE MOUNTED LEVEL SWITCH

NPT or Hex Nut	Up to 300 psi	Nylon Polypropylene Versaplast Zinc Stainless Steel	Lead Wires	-40 to +121°C
----------------	---------------	---	------------	---------------



## Single Point Level Sensors and Switches



Connections	Operating Pressures	Materials	Output	Max Working Temperature
<b>LS700F SPECIALTY LEVEL SWITCH</b>				
3/4" NPT	Up to 400 psi	Brass	Quick Connect	-40 to +105°C



<b>LS750 BILGE WATER LEVEL SWITCH</b>				
Liquid Tight Fitting	Up to 10 BAR	Brass	PVC Cable	-40 to +80°C



<b>LS77700 SINGLE POINT LEVEL SWITCH</b>				
1/8" NPT 3/8" UNF with nut	Up to 10 BAR	Brass Stainless Steel	Lead Wires	-40 to +150°C



<b>LS8005 BOTTLE TYPE LEVEL SWITCH</b>				
3/4" NPT	Up to 750 psi	Brass Stainless Steel	Lead Wires	-40 to +148.9°C



<b>NGS DUAL MAGNET FLOAT SWITCH</b>				
NPT, BSP or Flanged	Up to 25 BAR	Stainless Steel	Cable	Up to 250°C



<b>UCL510 CONTINUOUS LEVEL SENSOR</b>				
1" NPT 1" BSPP	Up to 30 psi	PVDF	4 - 20 mA Two Wire	-35 to +60°C



<b>UCL520 CONTINUOUS LEVEL SENSOR</b>				
2" NPT 2" BSPP	Up to 30 psi	PVDF	4 - 20 mA Two Wire	-20 to +71°C



<b>XLS1 ULTRASONIC LEVEL SENSOR</b>				
NPT, BSPP or Metric	Up to 250 psi	Stainless Steel	3-Pin Deutsch 3-Wire Output PVC Cable	-40 to +125°C

## Steam Traps



Connections	Nominal Pressure	Operating Pressures	Max KVS Values	Max Working Temperature
<b>KA NIAGARA FLOAT CONTROLLED STEAM TRAP</b>				
DN 15 - 150	PN16	0 - 16 BAR	193 m <sup>3</sup> /h	200°C



<b>KA2 FLOAT CONTROLLED STEAM TRAP</b>				
G 3/4" x 1/2"	PN16	0 - 2 BAR 0 - 6 BAR 0 - 12 BAR	350 l/h	190°C



### Steam Traps



Connections	Nominal Pressure	Operating Pressures	Max KVS Values	Max Working Temperature
<b>KA2K FLOAT CONTROLLED STEAM TRAP</b>				
G 1/2" x 1/2" G 3/4" x 1/2" G 1" x 3/4"	PN16	0 - 2 BAR 0 - 6 BAR 0 - 12 BAR	1570 l/h	80°C



<b>KA2X FLOAT CONTROLLED STEAM TRAP</b>				
DN 25 x G 3/4" G 1" x 3/4"	PN16	0 - 13 BAR	1200 l/h	190°C



<b>KA3 FLOAT CONTROLLED STEAM TRAP</b>				
DN 15 - 25	PN16	0 - 12 BAR	2000 l/h	190°C



<b>AS2 PIPELINE ANCILLARIES</b>				
DN 15 - 50 G 1/2" - 2"	PN16	0 - 13 BAR	Up to 1200 l/h	190°C

### Submersible Transducers



Pressure Type	Pressure Ranges	Pressure Fittings	Output	Accuracy
<b>2600 CVD PRESSURE TRANSDUCER</b>				
Gauge Absolute	Vacuum to 285 psi (Min - Max)	NPT, BSPP, BSPT SAE or Nose Cone	4 - 20 mA 100 mV 0 - 10 V Others on request	0.25% 0.15%



<b>4000 SPUTTERED FILM PRESSURE TRANSDUCER</b>				
Gauge Absolute Sealed Differential	0 to 10,000 psi (Min - Max)	NPT, BSPP, UNF, Metric or Nose Cone	4 - 20 mA	0.1% 0.08%



<b>5000 CAPACITANCE PRESSURE TRANSDUCER</b>				
Gauge	0.36 to 15 psi (Min - Max)	NPT, BSPP, UNF, Metric or Nose Cone	4 - 20 mA 0 - 5 VDC Others on request	0.25%



<b>6700 CVD PRESSURE TRANSDUCER</b>				
Gauge Compound Absolute	0 to 6,000 psi (Min - Max)	NPT, BSPP, UNF, Metric or Nose Cone	4 - 20 mA	0.15% 0.25%

LEVEL & TEMPERATURE



## Tank Bottom Valves



### BA/BAS TANK BOTTOM VALVE

Disc type valves either open into the vessel (BA) or valve (BAS). These can also be equipped with bellows and heating jacket and can be connected directly to the vessel or to the flange free of dead space. We can offer various bore sizes with replaceable seat sleeves and pneumatic diaphragm actuator (spring-closed) or ex-proof solenoid valve with limit switches. Please contact us with your specifications for a quote.



### BV/BVS TANK BOTTOM VALVE

We offer various designs of Piston type valves with either smooth piston/elastomeric seal (BV) or piston with metal-to-metal seat (BVS). These can also be equipped with heating jacket and can be connected directly to the vessel or to the flange free of dead space. We can offer various bore sizes with replaceable seat sleeves and electric actuators/ex-proof or pneumatic cylinder actuators. Please contact us with your specifications for a quote.

## Thermometers



Connections	Measuring Range
<b>DTE BATTERY POWERED DIGITAL THERMOMETER</b>	
NPT, BSPP, Tri-Clamp, RJT or IDF	-200 to +850°C



<b>HND-T125 PRECISION HANDHELD THERMOMETER</b>	
2-PIN Flat 4 PIN Mini DIN	220 to +1768°C



<b>HND-T215 PRECISION HANDHELD THERMOMETER</b>	
2-PIN Flat 4 PIN Mini DIN	-220 to +1768°C



<b>LTS RESISTIVE TEMPERATURE SENSOR</b>	
BSPP or Metric	-50 to +250°C



<b>TBE BI-METAL THERMOMETER</b>	
NPT or BSPP	-50 to +600°C



<b>TNF CAPILLARY THERMOMETER</b>	
NPT or BSPP	-40 to +600°C



<b>TWL RESISTANCE THERMOMETER</b>	
NPT or BSPP	-80 to +600°C

## Wires & Seals

**BSWS SENSOR WIRE SEALS**



**EG SINGLE ELECTRODE SEALING**



**EGT SINGLE ELECTRODE SEALING**



**HD HIGH DENSITY MULTIPLE WIRE FEEDTHROUGHS**



**HPEG HIGH PRESSURE SEALING ASSEMBLIES**



**HPPL HIGH PRESSURE SEALING ASSEMBLIES**



**MHC MULTIPLE ELEMENT SEALING**



**MHM MULTIPLE ELEMENT SEALING**



**MK SINGLE ELEMENT SEALING**



**PG SINGLE ELEMENT SEALING**



**PGS, SPG & DSPG SPLIT SEALS FOR PROBE SEALING**



**PL INSULATED LEADWIRE SEALING**



**TG BARE WIRE SEALING**



**TG24T INSULATED LEADWIRE SEALING**



**TGF/TGM HIGH TEMPERATURE SEALING**

