













2200 Series



Mini 4 Pin - No Connector	
Code B	
Mini 4 Pin - With Connector	
Code A	 1.02 26.02
IP67 Cable (Waterproof)	
Code F	 1.37 35.0
24 AWG Shielded PVC	
IP65 or NEMA4 Cable	
Code D or 2	 2.76 70.1
24 AWG Shielded PVC	

2600 Series












10-6 or 8-4 Mil-C Connector	
10-6 Code C	
8-4 Code 1	 0.87 22
Large DIN 43650 Plug	
Code G	 2.65 68 1.30 33
Conduit Connector with Cable	
Code 3	 1/2" NPT 49 1.70
24 AWG Shielded PVC	
Conduit Connector with Flying Leads	
Code 3	 1/2" NPT 1.70/43
with length "U"	
Moulded, Immersible Cable	
Code M	 0.90 23
24 AWG, Vent, Shielded, Polyurethane	

mV Gauge/Absolute Amplified Gauge
 2.43 61.60 MAX
Amplified Absolute
 2.48 63.7 MAX

Maximum diameter 1.07" (27.3 mm)

mV Gauge/Absolute Amplified Gauge
 2.00 53.2 MAX
Amplified Absolute
 2.54 64.4 MAX

Maximum diameter 1.07" (27.3 mm)

1/8-27 NPT	
Code 08	 0.50 13
1/4 - 18 NPT	
Code 02 with snubber	 0.79 20
Code 0J with snubber	 0.79 20
1/4-18 NPT Internal	
Code 0E	 0.95 24
1/2-14 NPT	
Code 0H	 1.02 26.0
7/16-20 UNF-2A	
Code 04	 0.75 19
9/16-18 UNF-2A	
Code 1P	 0.67 17
G 1/8 Internal	
Code 09	
G 1/4 External	
Code 01	 0.67 17
R 1/4	
Code 0A	 0.79 20
Nose Cone - Black Acetal	
Code 19	 0.75 19