

BOISWOOD GAS AND LIQUID CONTROL TECHNOLOGIES



sense line connection EO8

C=	max.	size	with	stressless	spring	
----	------	------	------	------------	--------	--



MA	NKE	NВE	KG

setting	size	nominal diameter DN									
range bar		15	20	25	40	50	65	80	100	125	150
all ranges	Α	130	150	160	200	230	290	310	350	400	480
	В	55	55	60	75	85	105	105	110	220	220
0.02-0.25	С	510	510	510	520	520	570	570	570	810	810
(0.05-0.25	C ₁	640	640	640	680	680	730	730	730	970	97(
> DN 125)	D	360	360	360	360	360	360	360	360	500	50
0.1 - 0.6	С	510	510	510	630	630	680	680	680	810	81
	C ₁	640	640	640	790	790	840	840	840	970	97
	D	270	270	270	360	360	360	360	360	360	36
0.2 - 1.2	С	510	510	510	630	630	680	680	680	810	810
	C ₁	640	640	640	790	790	840	840	840	970	970
	D	220	220	220	270	270	270	270	270	270	270
0.8 - 2.5	С	490	490	490	650	650	680	680	680	810	810
2 - 5	C ₁	620	620	620	810	810	840	840	840	970	97
4.5 - 10	D	175	175	175	220	220	220	220	220	220	220

UV4.1 SERIES